

SM5 Audio Surveillance Kit

Description

Single zone audio surveillance system designed to connect directly to an audio recorder, video recorder, DVR, CCTV monitor (with a built in speaker), remote monitoring equipment, etc.

Kit Includes

- SM1 Pre-amplified microphone.
- SM1 mounting screws.
- SM2 Interface adapter.
- 12 VDC AC adapter.
- 3' RCA or 3.5mm Patch cable.
- Warning label.
- Installation instructions.

Options

SPECIFY: RCA output connectors OR 3.5mm when ordering.

Wiring Requirements

- Stranded 22-gauge, 2-conductor shielded cable with drain wire.
Max. cable length: 1500'.

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning label in plain view is all that is required.

Warranty

1 year parts and labor.

Made in U.S.A.



SM1 Microphone Specifications

- Omni-directional Electret element. 25' range in all directions.
- Frequency response: 200-16Khz.
- Low noise MOSFET pre-amplifier.
- Line level, unbalanced output.
- Adjustable gain.
- Treble boost circuit. Selectable on/off. Enhances clarity of time lapse recordings.
- Limiter circuit. Selectable on/off.
- 3 position Euro-style connector makes cable termination fast and clean.
- Flush mountable. Can be mounted on a single gang electrical box.
- Power: 12 VDC @ 10mA
- See SM1 data sheet for more information.

SM2 Interface Adapter Specifications

- Standard RCA or 3.5mm (please specify) jack for connection to DVRs, etc.
- 3 position Euro-style connector makes cable termination fast and clean.
- LED power indicator.
- Power: 12 VDC @ 10mA
- Reverse polarity protected and fused.
- Dimensions L 2.7 x W 1.7 x H 1.2
- See SM2 data sheet for more information.